



GE's LED fixture
portfolio that
ships in 2 or 5 days




QUICKSHIP Portfolio

Indoor

BT/BR/BV/ET Series

2x2, 2x4, and EMBB
Surface mount kits (BT, BR, BV,
AB, AC, AD)



Refit Door Kit

2x2, 2x4



RX Series

6" & 8" – 1000, 1500, 2000 lm



DI Series

4" and 6" Round Housing
Infusion™ Light Modules
Reflectors



TS Series

Track Light



IS Series

Indirect suspended fixture
1x8 model



WS Series

4' Wrap fixture
Narrow and Wide Body



FM Series

Flush Mount Fixture



QUICKSHIP Portfolio

Outdoor

Evolve™ LED – E2SA
Security Light



Evolve™ LED – EANA
Area Site Light




Evolve™ LED – EFNA
Flood Light



Evolve™ LED – EG2R
Garage Light



Evolve™ LED – EWS2
Area Light
– Scalable Wall pack



Industrial

Albeo™ LED – ABR1
High Bay Luminaire



Albeo™ LED – ABV1
High Bay Luminaire



Albeo™ LED – ALR1
4' and 8' Linear Fixture



Albeo™ LED – ALV1
4' and 8' Linear Fixture



Indoor Fixtures

Lumination™ BT Series LED Luminaires



- Ideal for general indoor lighting in office, commercial, retail and education applications
- Fits perfectly into T-grid drop ceilings for easy high-tech retrofits
- Provides high uniformity across the lens
- Converts to surface mount with surface mount kit
- Available in 2x2, 1x4 and 2x4 models
- CCT: 3500K, 4000K
- Typical CRI of 80+
- 1x4: 42W at 4000-4200 lumens
- 2x2: 34W at 3300-3500 lumens
- 2x4: 43W at 4500-4700 lumens
- L70 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ BT Series LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
26821	BT220D3AVWHTTE	Recessed Backlit 2x2, Lambertian, 2000 lumen, 4000K, 0-10V	1-40	5 days	41-200	2 weeks
26822	BT220D2AVWHTTE	Recessed Backlit 2x2, Lambertian, 2000 lumen, 3500K, 0-10V	1-40	5 days	41-200	2 weeks
26941	BT240D3AVWHTTE	Recessed Backlit 2x4, Lambertian, 3000 lumen, 4000K, 0-10V	1-40	5 days	41-200	2 weeks
26973	BT240D2AVWHTTE	Recessed Backlit 2x4, Lambertian, 3000 lumen, 3500K, 0-10V	1-40	5 days	41-200	2 weeks
26790	BT220A3AVWHTTE	Recessed Backlit 2x2, Lambertian, 3300 lumen, 4000K, 0-10V	1-80	2 days	81-200	2 weeks
26798	BT220A2AVWHTTE	Recessed Backlit 2x2, Lambertian, 3300 lumen, 3500K, 0-10V	1-40	2 days	41-200	2 weeks
26835	BT220A3AVWHTTEEL	Recessed Backlit 2x2, Lambertian, 3300 lumen, 4000K, 0-10V, EL	1-20	2 days	21-80	2 weeks
26842	BT220A2AVWHTTEEL	Recessed Backlit 2x2, Lambertian, 3300 lumen, 3500K, 0-10V, EL	1-20	2 days	21-80	2 weeks
26843	BT240A3AVWHTTE	Recessed Backlit 2x4, Lambertian, 4700 lumen, 4000K, 0-10V	1-80	2 days	81-200	2 weeks
26844	BT240A2AVWHTTE	Recessed Backlit 2x4, Lambertian, 4500 lumen, 3500K, 0-10V	1-40	2 days	41-200	2 weeks
26845	BT240A3AVWHTTEEL	Recessed Backlit 2x4, Lambertian, 4700 lumen, 4000K, 0-10V, EL	1-20	2 days	21-80	2 weeks
26870	BT240A2AVWHTTEEL	Recessed Backlit 2x4, Lambertian, 4500 lumen, 3500K, 0-10V, EL	1-20	2 days	21-80	2 weeks

* Shipment time subject to inventory availability

Lumination™ BR Series LED Luminaires



- Ideal for general indoor lighting in office, commercial, retail and education applications
- Easy and quick install into T-bar ceiling grids
- Perfect for new construction, remodel or retrofit projects
- Drop down door with accessible components
- Converts to surface mount with surface mount kit
- Available in 1x4, 2x2 or 2x4 models
- CCT: 3500K, 4000K
- Typical CRI of 80+
- 1x4: 42W at 3800-4000 lumens
- 2x2: 34W at 3300-3500 lumens
- 2x4: 43W at 4700-5000 lumens
- L85 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ BR Series LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
94993	BR220A3AVWHTTE	Recessed Backlit Accessible Door 2x2, 3500 lumen, 4000K, 0-10V	1-80	5 days	81-200	2 weeks
94994	BR220A2AVWHTTE	Recessed Backlit Accessible Door 2x2, 3325 lumen, 3500K, 0-10V	1-40	5 days	41-200	2 weeks
95051	BR240A3AVWHTTE	Recessed Backlit Accessible Door 2x4, 5000 lumen, 4000K, 0-10V	1-80	5 days	81-200	2 weeks
95053	BR240A2AVWHTTE	Recessed Backlit Accessible Door 2x4, 4750 lumen, 3500K, 0-10V	1-40	5 days	41-200	2 weeks

* Shipment time subject to inventory availability

Lumination™ BV Architectural Series LED Luminaires



- Provides visual appeal ideal for office, retail, or any space that requires a three dimensional look
- Curving and delineated details add creative appeal
- High uniformity across the lens
- Converts to surface mount with surface mount kit
- Access to components from beneath the ceiling
- Available in 2x2 and 2x4 models
- CCT: 3500K, 4000K
- Typical CRI of 80+
- 2x2: 33W at 3200-3250 lumens
- 2x4: 48W at 5100-5200 lumens
- L85 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ BV Architectural Series LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
27075	BV220A3AVWHTTE	Recessed Backlit BV Door 2x2, 3250 lumen, 4000K, 0-10V	1-20	5 days	21-80	2 weeks
27084	BV220A2AVWHTTE	Recessed Backlit BV Door 2x2, 3200 lumen, 3500K, 0-10V	1-20	5 days	21-80	2 weeks
27482	BV240A3AVWHTTE	Recessed Backlit BV Door 2x4, 5200 lumen, 4000K, 0-10V	1-20	5 days	21-80	2 weeks
64096	BV240A2AVWHTTE	Recessed Backlit BV Door 2x4, 5100 lumen, 3500K, 0-10V	1-20	5 days	21-80	2 weeks

* Shipment time subject to inventory availability



Indoor Fixtures

Lumination™ ET Series LED Luminaires



- Advanced edge lit LED optical system provides high uniformity, excellent efficiency, improved spacing criteria, and reduced glare
- Easily installs in the most commonly used T-bar ceiling grids
- Diffused lens gives an evenly illuminated appearance
- May come equipped with Intrinsix™ technology which provides uniform light distribution
- Available in 1x4, 2x2, and 2x4 models
- CCT: 3000K, 3500K, 4000K
- Typical CRI of 80+
- 1x4: 47W at 3800-4000 lumens
- 2x2: 42W at 3500-3900 lumens
- 2x4: 47-54W at 3800-4500 lumens
- L85 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ ET Series LED Luminaires. For more in-depth information, please visit gelighting.com.




Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
69278	ET220A3AVWHTTE	Recessed EdgeLit 2x2, Lambertian, 3250 lumen, 4000K, 0-10V	1-40	5 days	41-200	2 weeks
69277	ET220A2AVWHTTE	Recessed EdgeLit 2x2, Lambertian, 3200 lumen, 3500K, 0-10V	1-20	5 days	21-200	2 weeks
67603	ET240A3AVWHTTE	Recessed EdgeLit 2x4, Lambertian, 5200 lumen, 4000K, 0-10V	1-20	5 days	21-80	4 weeks
67602	ET240A2AVWHTTE	Recessed EdgeLit 2x4, Lambertian, 5100 lumen, 3500K, 0-10V	1-20	5 days	21-80	4 weeks

* Shipment time subject to inventory availability

Lumination™ LED Surface Mount Kit



- Converts recessed fixture to surface mount
- Universal installation for any of the recessed series that offers simple installation without ordering different luminaires
- Provides high uniformity across the lens
- Includes capability for fixture with emergency battery
- White finish
- Available in 1x4, 2x2, and 2x4 models
- 1x4: BT or BR, BV, AB, AC kits
- 2x2: BT or BR, BV, AB, AC kits
- 2x4: BT or BR, BV, AB, AC kits

The descriptions above represent the entire portfolio of Lumination™ LED Surface Mount Kits. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
212462	B22 SMK	2x2 Surface Mount Kit for BT	1-20	2 days	21-80	2 weeks
212463	B24 SMK	2x4 Surface Mount Kit for BT	1-20	2 days	21-80	2 weeks
212459	A22 SMK	2x4 Surface Mount Kit for BR, BV, AB, AC, AD Recessed Fixtures	1-20	2 days	21-80	2 weeks
212460	A24 SMK	2x4 Surface Mount Kit for BR, BV, AB, AC, AD Recessed Fixtures	1-20	2 days	21-80	2 weeks

* Shipment time subject to inventory availability

Lumination™ LED Refit Door Kit



- LED upgrade for Linear Fluorescent Fixtures
- Simple and fast installation
- Reduced glare
- Provides high uniformity, great efficiency and reduced glare
- Available in 2x2 and 2x4 models (1x4 custom)
- CCT: 3500K, 4000K
- Typical CRI of 80+
- 2x2: 21W at 1950-2000 lumens
- 2x4: 21W at 1950-2000 lumens
- L70 @ 50,000 hours
- 0-10V Dimming

The descriptions above represent the entire portfolio of Lumination™ LED Refit Door Kits. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
208160	LED20/DK22/835/10/SO	Refit Door Kit 2x2, 1950 lumen, 3500K	1-20	2 days	21-80	2 weeks
208161	LED20/DK22/840/10/SO	Refit Door Kit 2x2, 2000 lumen, 4000K	1-40	2 days	41-80	2 weeks
208162	LED35/DK24/835/10/SO	Refit Door Kit 2x4, 3900 lumen, 3500K	1-20	2 days	21-80	2 weeks
208163	LED35/DK24/840/10/SO	Refit Door Kit 2x4, 4100 lumen, 4000K	1-80	2 days	81-200	2 weeks

* Shipment time subject to inventory availability



Indoor Fixtures

Lumination™ RX Series LED Downlights



- Ideal for office, retail, hospitals, schools, airports, government facilities and shopping malls
- Visually pleasing and energy efficient
- Great solution to replace 1 or 2-lamp CFL downlights
- Extremely quick and easy installation into most 6-inch and 8-inch CFL rough-in frames
- CCT: 3000K, 3500K, 4000K
- Typical CRI of 80+
- 6 inch: 14W at 1000 lumens
- 8 inch: 14W at 1000 lumens;
- 19.5W at 1500 lumens; 25W at 2000 lumens
- L70 @ 50,000 hours
- Non-dimming

The descriptions above represent the entire portfolio of Lumination™ RX Series LED Downlights. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
212702	RX610830MV	6" Round 3000K 1000 lumen	1-160	5 days	161-320	2 weeks
212703	RX610835MV	6" Round 3500K 1000 lumen	1-160	5 days	161-320	2 weeks
212704	RX610840MV	6" Round 4000K 1000 lumen	1-160	2 days	161-320	2 weeks
212705	RX810830MV	8" Round 3000K 1000 lumen	1-160	5 days	161-320	2 weeks
212706	RX810835MV	8" Round 3500K 1000 lumen	1-160	5 days	161-320	2 weeks
212707	RX810840MV	8" Round 4000K 1000 lumen	1-160	2 days	161-320	2 weeks
212708	RX815830MV	8" Round 3000K 1500 lumen	1-160	5 days	161-320	2 weeks
212709	RX815835MV	8" Round 3500K 1500 lumen	1-160	5 days	161-320	2 weeks
212710	RX815840MV	8" Round 4000K 1500 lumen	1-160	2 days	161-320	2 weeks
212711	RX820830MV	8" Round 3000K 2000 lumen	1-160	5 days	161-320	2 weeks
212712	RX820835MV	8" Round 3500K 2000 lumen	1-160	5 days	161-320	2 weeks
212713	RX820840MV	8" Round 4000K 2000 lumen	1-160	2 days	161-320	2 weeks

* Shipment time subject to inventory availability

Lumination™ DI Series LED Downlights



- Ideal for retail, office and hospitality applications
- Choose the perfect lumen output, color temperature and optical distribution for your project
- Changeable lighting module that can be scaled for any environment
- Available in four color temperatures and five lumen packages, all with 90+ CRI
- Reflector is available in narrow, medium and wide light distribution patterns
- Available in 4 inch and 6 inch round or square luminaires, wall washing is an option
- CCT: 2700K, 3000K, 3500K, 4000K
- Typical CRI of 90
- 4 inch: 14W at 10,000 lumens; 25W at 20,000 lumens
- 6 inch: 14W at 10,000 lumens; 51W at 40,000 lumens
- L85 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ DI Series LED Downlights. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
83624	DI4RLL1V10HO	4" Round Housing, Low-Lumen, 120V, 0-10V	1-40	5 days	41-80	2 weeks
83625	DI4RLL2V10HO	4" Round Housing, Low-Lumen, 277V, 0-10V	1-40	5 days	41-80	2 weeks
83630	DI6RLL1V10HO	6" Round Housing, Low-Lumen, 120V, 0-10V	1-40	5 days	41-80	2 weeks
83632	DI6RLL2V10HO	6" Round Housing, Low-Lumen, 277V, 0-10V	1-40	5 days	41-80	2 weeks
83633	DI6RHL1V10HO	6" Round Housing, High-Lumen, 120V, 0-10V	1-40	5 days	41-80	2 weeks
83638	DI6RHL2V10HO	6" Round Housing, High-Lumen, 277V, 0-10V	1-40	5 days	41-80	2 weeks
19394	DLM1000/935	Light Module 1000 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
19485	DLM1500/935	Light Module 1500 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
19525	DLM2000/935	Light Module 2000 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
19595	DLM3000/935	Light Module 3000 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
34185	DLM4000/935	Light Module 4000 lumen, 90 CRI, 3500K	1-40	5 days	41-80	2 weeks
93984	RD14RWSDMR	4" Round Reflector, Wide, Semi-Diffuse, Polished Flange	1-80	5 days	81-200	2 weeks
93988	RD16RNSDMR	6" Round Reflector, Narrow, Semi-Diffuse, Polished Flange	1-80	5 days	81-200	2 weeks
93990	RD16RWSDMR	6" Round Reflector, Wide, Semi-Diffuse, Polished Flange	1-80	5 days	81-200	2 weeks

* Shipment time subject to inventory availability



Indoor Fixtures

Lumination™ TS Series LED Track Lights



- Efficient upgrade from CMH and PAR lamps
- delivers impressively high light levels in a sleek, compact design
- Choose from options including a wide range of lumen packages, color temperatures and beam distributions
- Available in white, black and silver
- 3 different track adaptors: Juno, Global, Lightoiler
- Equipped with the GE "Visual Comfort" lens
- Energy efficient flood versions @ 90 LPW
- 1-Circuit Global track and accessories available
- Spot version capable of 16,000 CBCP
- L70 @ 50,000 hours
- reveal® Whiter White™ technology available
- CCT: 2700, 3000 and 3500K

The descriptions above represent the entire portfolio of Lumination™ TS Series LED Track Lights. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
207909	TS1L2FL830WG11V	Track Head, 1300 lumen, Flood, 3000K, 80 CRI, White, Global Adapter	1-20	2 days	21-80	2 weeks
207910	TS1L2FL830BG11V	Track Head, 1300 lumen, Flood, 3000K, 80 CRI, Black, Global Adapter	1-20	2 days	21-80	2 weeks
207949	TS1L2FL830WJ11V	Track Head, 1300 lumen, Flood, 3000K, 80 CRI, White, Juno Adapter	1-20	2 days	21-80	2 weeks
207950	TS1L2FL830BJ11V	Track Head, 1300 lumen, Flood, 3000K, 80 CRI, Black, Juno Adapter	1-20	2 days	21-80	2 weeks

* Shipment time subject to inventory availability

Lumination™ IS Series Suspended LED Luminaires



- Suspended fixtures ideal for settings with an open-ceiling design
- Quick and easy installation
- Continuous run (up to 400-ft) with 1 power drop
- Indirect illumination with uniform lit appearance
- Available in 4' or 8' models
- CCT: 3000, 3500, 4000, and 5000K
- Typical efficiency: 125 LPW
- Lumen levels available: 8,000-24,000 lumens
- L85 @ 75,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Lumination™ IS Series Suspended LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
83475	ISC80A3MVWHITE	8' Linear Indirect Suspended, 8400 lumen, 4000K, 120-277, 0-10V	1-160	2 days	161-400	2 weeks
93018007	IS Starter Kit	2x end caps, power harness, dimming harness	1-20	2 days	21-80	2 weeks

* Shipment time subject to inventory availability

Lumination™ WS Series Surface Mount LED Luminaires



- Commercial ceiling fixture that provides high quality, excellent efficiency and reduced glare in cooler and wash down applications
- Upgrade to the Linear Fluorescent Fixture
- High uniformity
- Available in 2x2 and 2x4 models (1x4 custom)
- CCT: 3500K, 4000K

The descriptions above represent the entire portfolio of Lumination™ WS Series Surface Mount LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
26722	WS4N0A3SVWHITE	Wrap 4'x7" (Narrow Body) Lambertian 0-10V	1-40	2 days	41-80	2 weeks
26787	WS4W0A3SVWHITE	Wrap 4'x14" (Wide Body) Lambertian 0-10V	1-40	2 days	41-80	2 weeks

* Shipment time subject to inventory availability

Lumination™ FM Series Surface Mount LED Luminaires



- Ideal for hospitality, office, and residential applications in retrofit and new construction
- Quick installation with included mounting brackets and hardware
- Light is distributed evenly without pixilation resulting in a soft glow around the fixture
- ENERGY STAR® certified
- CCT: 2700K
- Typical CRI of 80
- L70 @ 25,000 hours
- Input Power; 15W
- 65 LPW
- Non-dimming

The descriptions above represent the entire portfolio of Lumination™ FM Series Surface Mount LED Luminaires. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
33741	LED15FMM9-W	9in Surface Light	1-80	5 days	81-200	2 weeks
20433	LED15FMM12-W	12in Surface Light	1-80	5 days	81-200	2 weeks

* Shipment time subject to inventory availability



Outdoor Fixtures

Evolve™ LED Security Light – E2SA



- Ideal for outdoor work yards, roadside commercial establishments, suburban developments and rural areas
- Built to withstand harsh elements
- Die-cast aluminum housing
- Structured LED arrays for optimized type 3 and type 5 square distributions
- CCT: 4000K
- Typical CRI of 70
- L70 @ 100,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Evolve™ LED Security Light – E2SA. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93023249	E2SA0A1B31402NN	Security, 120V-277V, 3,600 Lumens, 4000K	1-10	5 days	11-99	2 weeks
215014	E2SA0B1B31402NN	Security, 120V-277V, 5,200 Lumens, 4000K	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability

Evolve™ LED Area Light – EANA



- Ideal for site, area, and general lighting applications
- Provides uniformity, vertical light distribution, reduced on-site glare and effective security light levels
- Obtain efficient parking space with dimming and occupancy sensing features
- Multiple mounting options
- CCT: 4000K
- Typical CRI of 70
- Temperature rated at -40° to 50°C
- DLC Listed
- L85 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Evolve™ LED Area Light – EANA. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93026611	EANA0D35401CDKBZ	Area, 120V-277V, Asymmetric Wide, 9,600 Lumens, 4000K, Bronze	1-10	5 days	11-99	2 weeks
93026613	EANA0F35401CDKBZ	Area, 120V-277V, Asymmetric Wide, 13,400 Lumens, 4000K, Bronze	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability

Evolve™ LED Flood Light – EFNA



- Ideal for flood lighting applications including: Billboard/bulletin, spot and flag poles, building façade' and general parking
- Die-cast aluminum housing incorporating heat sink
- Reflective technology to optimize efficiency and minimize glare
- Multiple mounting options
- CTT: 4000K
- Typical CRI of 70
- Temperature rated at -40° to 50°C
- DLC Listed
- L85 @ 50,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Evolve™ LED Flood Light – EFNA. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
209106	EFNA0F35401KDKBZ	Flood, 120V-277V, Asymmetric Wide, 13,400 Lumens, 4000K Bronze	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability



Outdoor Fixtures

Evolve™ LED Garage Light – EG2R



- Ideal for garage, warehouse, walkway and stairway lighting
- Die-cast aluminum housing incorporating heat sink
- Provides high uniformity and vertical light distribution
- Features programmable motion sensing, step dimming and daylight harvesting
- Standard color: White
- Available with seven different mounting options
- CCT: 4000K, 5000K
- Typical CRI of 70
- Temperature rated at -40° to 50°C
- DLC Listed
- L70 @ 100,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Evolve™ LED Garage Light – EG2R. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
210737	EG2R0A5PS5011WHITE	Garage, 120V-277V, 5,000 Lumens, 5000K, White, Pendant Mount	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability

Evolve™ LED Area Light Scalable Wall Pack – EWS2



- Ideal for wall mounted, site, area, and general lighting applications
- Provides uniformity, vertical light distribution, reduced offsite visibility/on-site glare and effective security light levels
- Die-cast aluminum housing
- CCT: 4000K, 5000K
- Typical CRI of 70
- Temperature rated at -40° to 50°C
- DLC Listed
- L85 @ 50,000 hours

The descriptions above represent the entire portfolio of Evolve™ LED Area Light Scalable Wall Pack – EWS2. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
215362	EWS20A7D1401DKBZ	Wall Pack, 120V-277V, Asymmetric Forward, 3,100 Lumens, 4000K, Bronze	1-10	5 days	11-99	2 weeks
216115	EWS20C7D1501DKBZ	Wall Pack, 120V-277V, Asymmetric Forward, 4,800 Lumens, 5000K, Bronze	1-10	5 days	11-99	2 weeks

* Shipment time subject to inventory availability



Industrial Fixtures

Albeo™ LED Luminaire – ABR1



- IP66 rated fixture for industrial environments with high ambient temperatures and wet applications
- Modular design: single and double fixture options
- Cable/chain, rod or pendant mount
- Daylight and motion controls

- CCT: 5000K
- Typical CRI of 70
- Lumen output: 9,000-46,000 lm
- L70 @ 100,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Albeo™ LED Luminaire – ABR1. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
93014044	ABR101H571NNSTANW	Highbay, 120-277V, 11,800 Lumens, 5000K, 120, 70 CRI, White	1-5	5 days	6 - 200	2 weeks
93014051	ABR101T571NNSTANW	Highbay, 120-277V, 8,800 Lumens, 5000K, 120, 70 CRI, White	1-5	5 days	6 - 200	2 weeks
213915	ABR102H571NNSTANW	Highbay, 120-277V, 23,000 Lumens, 5000K, 120, 70 CRI, White	1-5	5 days	6 - 200	2 weeks

* Shipment time subject to inventory availability

Albeo™ LED Luminaire – ABV1



- Ideal for warehouse, cold storage, industrial, gymnasium, sports arena, retail, and high-ceiling applications
- Modular design: 1 and 2 modules
- Combination of steel and aluminum housing
- Daylight and motion controls

- CCT: 4000K, 5000K
- Typical CRI of 70
- Lumen output: 9,000-24,000 lm
- L70 @ 100,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Albeo™ LED Luminaire – ABV1. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time*	Lot Size	Lead Time*
208574	ABV101T471NVSTKNW1PK	Highbay, 120-277V, 9,000 Lumens, 4000K, 120, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
208570	ABV101T571NVSTKNW1PK	Highbay, 120-277V, 9,100 Lumens, 5000K, 120, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
208575	ABV101V471NVSTKNW1PK	Highbay, 120-277V, 12,000 Lumens, 4000K, 120, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
208571	ABV101V571NVSTKNW1PK	Highbay, 120-277V, 12,300 Lumens, 5000K, 120, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
208576	ABV102T471NVSTKNW1PK	Highbay, 120-277V, 18,000 Lumens, 4000K, 120, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
208572	ABV102T571NVSTKNW1PK	Highbay, 120-277V, 18,300 Lumens, 5000K, 120, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
208577	ABV102V471NVSTKNW1PK	Highbay, 120-277V, 24,100 Lumens, 4000K, 120, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
208573	ABV102V571NVSTKNW1PK	Highbay, 120-277V, 24,600 Lumens, 5000K, 120, 70 CRI, White	1-10	5 days	11 - 800	2 weeks
205004	ABV1 PENDANT MOUNT KIT	ABV1 Pendant Mount Kit, White	1-10	5 days	11 - 800	2 weeks
209104	ABV1 ROD MOUNT KIT	ABV1 Rod Mount Kit, White	1-10	5 days	11 - 800	2 weeks

* Shipment time subject to inventory availability



Industrial Fixtures

Albeo™ LED Luminaire – ALR1



- Ideal for low bay and task level applications in commercial, industrial, warehouse, office and education settings
- IP65 rated
- IP66 rated motion sensors
- Fiberglass housing with diffuser
- Chain or surface mount
- Available in 4' and 8' models
- CCT: 4000K, 5000K
- Typical CRI of 70
- Lumen output: 3,300-14,800 lm
- L70 @ 100,000 hours
- 0-10V dimming

The descriptions above represent the entire portfolio of Albeo™ LED Luminaire – ALR1. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time	Lot Size*	Lead Time*
216582	ALR101H4714SNNSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 Lumens, 4000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216579	ALR101H5714SNNSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 Lumens, 5000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216581	ALR101T4714SNNSTKNW1PK	Linear, 120V - 277V, 4' Length, 3,300 Lumens, 4000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216578	ALR101T5714SNNSTKNW1PK	Linear, 120V-277V, 4' Length, 3,300 Lumens, 5000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216583	ALR101V4718SNNSTKNW1PK	Linear, 120V-277V, 8' Length, 14,800 Lumens, 4000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216580	ALR101V5718SNNSTKNW1PK	Linear, 120V-277V, 8' Length, 14,800 Lumens, 5000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks

* Shipment time subject to inventory availability

Albeo™ LED Luminaire – ALV1



- Ideal for low bay and task level applications in commercial, industrial, warehouse, office and education settings
- Recommended for low bay lighting at 20 ft. or lower
- Stamped metal housing
- Chain/cable or surface mount
- Available in 4' and 8' models
- CCT: 4000K, 5000K
- Typical CRI of 70
- Lumen output: 3,350-14,800
- L70 @ 100,000 hours

The descriptions above represent the entire portfolio of Albeo™ LED Luminaire – ALV1. For more in-depth information, please visit gelighting.com.



Small Lot

SKU #	Cat Logic	Description	Lot Size	Lead Time	Lot Size*	Lead Time*
216576	ALV101H4714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 Lumens, 4000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216573	ALV101H5714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 5,300 Lumens, 5000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216575	ALV101T4714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 3,300 Lumens, 4000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216572	ALV101T5714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 3,300 Lumens, 5000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216577	ALV101V4714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 7,300 Lumens, 4000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks
216574	ALV101V5714SNVSTKNW1PK	Linear, 120V-277V, 4' Length, 7,300 Lumens, 5000K, 70 CRI, White	1-5	5 days	6 - 200	2-3 weeks

* Shipment time subject to inventory availability





www.gelighting.com

GE and the GE Monogram are trademarks of the General Electric Company. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company.
© 2016 GE.

15-0291 (Rev. 02/22/2016)